






OZNACZENIE		D1		D3		D4		D5		D6		D6*	
SCHEMAT													
		EI6C		EI30									
		L	P	L	P	L	P	L	P	L	P	L	P
WYMIAR W ŚWIETLE OŚCIEŻY	S <sub>0</sub>	112		100		100		90		100			
	H <sub>0</sub>	205		205		207		207		207			
WYMIAR W ŚWIETLE OŚCIEŻNICY	S	100		90		90		80		90			
	H	200		200		203		203		203			
PARTER		-	2	1	4	-	-	1	-	4*	2*		
I PIĘTRO		-	-	2	2	-	-	1	-	3*	1*		
II PIĘTRO		-	1	-	1	3	9	-	1	2*+2	2*+1		
RAZEM		-	3	3	7	3	9	2	1	9*+2	5*+1		
UWAGI		-DRZWI STALOWE, PLYTOWE kolor SZARY -KLASA ODP.OGNIOWEJ EI60 -DRZWI ZAOPATRZEĆ W SAMOZAMYKACZ -ZAMEK NA WKŁADKĘ PATENIOWĄ -OŚCIEŻNICA STALOWA		-DRZWI STALOWE, PLYTOWE kolor SZARY -KLASA ODP.OGNIOWEJ EI30 -DRZWI ZAOPATRZEĆ W SAMOZAMYKACZ -ZAMEK NA WKŁADKĘ PATENIOWĄ -OŚCIEŻNICA STALOWA		-DRZWI PLYTOWE -OKLEINA CPL HQ 0,7 mm kolor SZARY -OŚCIEŻNICA STALOWA REGULOWANA		-DRZWI PLYTOWE -OKLEINA CPL HQ 0,7mm kolor SZARY -OŚCIEŻNICA STALOWA REGULOWANA -KRATKA WENTYLACYJNA o pow.min. 0,022m <sup>2</sup> ,		-DRZWI PLYTOWE -OKLEINA CPL HQ 0,7mm kolor SZARY -OŚCIEŻNICA STALOWA REGULOWANA -KRATKA WENTYLACYJNA o pow.min. 0,022m <sup>2</sup> , -DRZWI ZAOPATRZEĆ W SAMOZAMYKACZ			